


Media: air – water – gas – vacuum
 Pressure range: 0 to 150 Bar max
 Media temperature: +180°C max*
 Ambient temperature: -20°C to +60°C
 Media viscosity: 50 centistokes max
 Mounting: any position
 Weight: 1750g per set



2/2 Stainless

1/8 & 1/4 MANIFOLD

NORMALLY CLOSED

2 WAY DIRECT ACTING

0 – 150 Bar

TYPE ADFS6/8000



PRESSURE

Ø Port BSP	Ø Orifice (mm)	Flow Kv Ltr/ min	Pressure Rating (Bar) ΔP			Coil	Seals	Part Number	
			Min	Max AC	Max DC				
1/8 ADFS6000	1.2	1.1	0	60	42	WPG1	NBR +80°C SILICONE +120°C EPDM +120°C FKM +120°C *VST +180°C (30 Bar Max) *PTFE +180°C (150 Bar)	ADFS6/8012 + seal + voltage	
	1.6	1.5	0	40	28			ADFS6/8016 + seal + voltage	
	2.0	1.8	0	20	15			ADFS6/8020 + seal + voltage	
	1/4 ADFS8000	1.2	1.1	0	120	84		WPG2	ADFS6/8112 + seal + voltage
		1.6	1.6	0	60	42			ADFS6/8116 + seal + voltage
		2.0	1.8	0	30	21			ADFS6/8020 + seal + voltage
WPA3C		3.0	4.3	0	20	14		ADFS6/8130 + seal + voltage	
		4.0	9.7	0	12	8.4		ADFS6/8140 + seal + voltage	
		5.0	10.7	0	10	7		ADFS6/8150 + seal + voltage	
	1.2	1.1	0	150	105	ADFS6/8212 + seal + voltage			
	1.6	1.5	0	80	56	ADFS6/8216 + seal + voltage			
2.0	1.8	0	60	42	ADFS6/8220 + seal + voltage				
3.0	4.3	0	40	28	ADFS6/8230 + seal + voltage				
4.0	9.7	0	20	14	ADFS6/8240 + seal + voltage				
5.0	10.7	0	15	10.5	ADFS6/8250 + seal + voltage				

OPTIONS

WPG IP67 (EN60529:1991+A1:2000) UL & CSA Approved Coil & IP65 LED Connector PG11 – DIN 43650 A, WPA3C IP54
 316 stainless steel manifold 1/8 BSP port (2 – 9 Sets)
 ATEX EExmII T4 II 2G & 2D IP65 T130°C coil. ⚠️ (Pressure rating WPG1 same, WPG2 70% of DC rating, WPA3C not available)
 NPT Thread
 *PTFE Seal

ELECTRICAL DATA

Voltage (-10% + 10%) Continuous duty 100%		Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
~	=		Inrush	Holding			
~	24 - 48 - 110 - 220 - 380 (50 or 60 Hz)	WPG1	11.2VA	8.2VA	H 180°C	IP 65 with connector	3 spades DIN 43650 DIN 40050 VDE 0110
=	12 - 24 - 48 (DC)		12 Watts				
~	24 - 48 - 110 - 220 - 380 (50 or 60 Hz)	WPG2	18.7VA	15.3VA			
=	12 - 24 - 48 (DC)		18 Watts				
~	24 - 48 - 110 - 220 - 380 (50 or 60 Hz)	WPA3C	88VA	57VA	N 200°C	IP54	30cm flying lead wires
=	12 - 24 (DC)		33.6 Watts				

CONSTRUCTION

Body : 316 stainless steel
 Tube and internal parts : Stainless steel
 Seals and gaskets: NBR, EPDM, Viton, Silicone or PTFE
 Moulded coil WPG : Resin, WPA3C round metal enclosure

REPAIR KIT

Armature	SP + Valve Part Number + ARMATURE
Coil	WPG1, WPG2 or WPA3C + voltage

OVERALL DIMENSIONS

