


Media: Air – Gas – Fluid - water
 Pressure range: 0 to 70 bar max
 Media temperature: +100 °C max
 Ambient temperature: -10 °C to +50 °C max
 Media viscosity: 40 centistokes max
 Mounting: Any Position
 Weight (including coil): 380 g
 Opening or closing time: 20 mSec max



3/2 Stainless

1/4

NORMALLY CLOSED

3 WAY PILOT ACTING

25 – 70 Bar

TYPE EN56651



PRESSURE

Ø Port BSP	Ø Orifice (mm)	Flow		Pressure Rating (bar) ΔP		Seals	Part Number
		Kv Ltr/min		Min	Max		
1/4	A 2.0	2 → 1	1.8	25	70	Polyurethane + FKM	EN56651-23 + voltage
	E 0.7	1 → 3	1.3				

OPTIONS

IP65 Coil + Connector PG9 – DIN 43650 A
 NPT 1/4 Thread

ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%	Coil	Power Consumption	Insulation class	Enclosure	Electrical connections
~ 12 - 24 - 48 - 110 - 230 (with rectifier)	31037	13.7 Watts	F 155°C	IP 65 with connector	3 spades DIN 43650 DIN 40050 VDE 0110
= 12 - 24 - 48 - 110 - 230 (DC)					

CONSTRUCTION

Body: Stainless steel
 Tube and internal parts: Stainless steel
 Seals and gaskets: Polyurethane and FKM
 Moulded coil: Resin

REPAIR KIT

Coil	31037 + voltage
Complete plunger + O' rings	KIT + valve part number

OVERALL DIMENSIONS

