


Media: air - gas
 Inlet Pressure: 45 Bar max
 Outlet Pressure: 0.5 – 30 Bar
 Media temp: -10°C to +70°C
 Ambient temp: -10° to +70°C
 Mounting: upright (USR any)



Stainless F R L

1/4 – 1/2

316 Stainless Steel

Manual, Semi, Fully Auto Drain

0.5 – 45 Bar

TYPE USFRL02-03-04



PRESSURE

Ø Port BSP	Max Flow Air L/min @ 6Bar (ANR)	Kg	Outlet Pressure (Bar)		Combination	Part Number
			Min	Max		
1/4(02)	2080,2200,2500	3.8	0.5	12	F/R+L	USFR/LB + port
			12	30		USFR/L + port
3/8(03)	2200,2500,3800	2	0.5	12	Filter/Regulator	USFRB + port
			12	30		USFR + port
1/2(04)	2440,2450,3030	1.65	0.5	30	Filter	USF + port
	1950,2250,2520		0.5	12	Regulator	USRB + port
	2500,2525,4100	1.4	12	30	Regulator	USR + port
		1.75	0.5	30	Lubricator	USL + port

OPTIONS

5 Micron SUS316 Filter Element (USFRL, USFR + USF)
 40 Micron SUS316 Filter Element (C) (USFRL, USFR, USF)
 Semi-Automatic drain (S) below 0.5 bar (USFRL, USFR, USF)
 Fully Automatic Drain (D) (USFRL, USFR, USF)
 Pressure Gauge, Blanking Plug, Mounting Bracket and Screws (USFRL, USFR, USR)
 NPT Thread

CONSTRUCTION

Body, Regulator, Filter (110cc) Lubricator (130cc) Bowl, Filter Elements, Mounting Bracket, Blanking Plug: 316 Stainless Steel
 Pressure gauge: cover 304 Stainless Steel / Thread 316 Stainless Steel
 O rings: Viton
 Test Pressure: 60 Bar

OVERALL DIMENSIONS

