


Media: air - gas
 Inlet Pressure: 45 Bar max
 Outlet Pressure: 0.5 – 28 Bar
 Media temp: -10°C to +70°C
 Ambient temp: -10°C to +70°C
 Mounting: Upright (USR any)
 Weight: 7960g



Stainless F R L

3/4 – 1

316 Stainless Steel

Manual, Semi or Auto Drain

0.5 - 45 Bar

TYPE USFR/L06-08



PRESSURE

Ø Port BSP	Max Flow Air L/min @ 6Bar (ANR)	Kg	Outlet Pressure (Bar)		Combination	Part Number	
			Min	Max			
3/4(06)	7600,8000	10.34	0.5	12	F+R+L	USF+R+LB + port	
	15200		12	28		USF+R+L + port	
	7600,8000	7.96	0.5	12	F/R + L	USF/R+LB + port	
	15200		12	28		USF/R+L + port	
	1(08)	8700	4.58	0.5	12	F/R	USF/RB + port
		9100		12	28		USF/R + port
1(08)	9600	3.95	0.5	12	Filter	USFB + port	
	19200		0.5	28		USF + port	
1(08)	9000,9400	3.4	0.5	12	Regulator	USRB + port	
	18000,22000		12	28		USR + port	
1(08)	13200	3.36	0.5	12	Lubricator	USLB + port	
	26400		5	30		USL + port	

OPTIONS

5 Micron Filter Element, Semi auto Drain, Pressure Gauge, Mounting Brackets + screws (USFRL, USF/R, USF)
 40 Micron Filter Element (C) (USFRLB, USF/R+LB, USFRB, USFB)
 Manual drain (H) (USFRLB, USF/R+LB, USFRB, USFB)
 Fully automatic drain (D) (USFRLB, USF/R+LB, USFRB, USFB)
 Bowl Viewer (W) (USFRLB, USF/R+LB, USFRB, USFB, USLB 0.5 to 12 Bar Only)
 NPT Thread

CONSTRUCTION

Body, Regulator, Filter (200cc), Lubricator Bowl (220cc), Mounting Bracket, Blanking Plug, Filter Element: 316 Stainless Steel
 Pressure gauge: Case 304 Stainless Steel / Thread 316 Stainless Steel
 O rings: Viton
 Test Pressure : USFRL 60 Bar USFRLB 15 Bar

OVERALL DIMENSIONS

