


Material according to EN161  
 Class: A Group: 2 Media: gas  
 Pressure range: 0 to 0.2 bar max  
 Ambient temperature: -15° to +60° C max  
 Mounting: any position  
 Weight (including coil): 270g  
 Opening time: less than 1 second  
 Closing time: less than 1 second



# 2/2 Brass

## 1/4

### NORMALLY CLOSED

### EN161 GAS APPROVED

### 0 – 200 mBar

## TYPE VMR010TN



#### PRESSURE

Ø Port BSP	Ø Orifice (mm)	Flow Kv Ltr/Min	Pressure Rating (mBar) ΔP		Seals	Part Number
			Min	Max		
1/4	6.0	9.16	0	200	NBR	VMR010TN-230vAC

#### OPTIONS

IP65 Coil & Connector PG9 – DIN 43650 A  
 12vAC, 12vDC, 24vAC, 24vDC, 110vAC or 110vDC  
 NPT Thread

#### ELECTRICAL DATA

Voltage (-15% + 10%) Continuous duty 100%		Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
~	=		Inrush	Holding			
~	12 - 24 - 110 - 230 (50 or 60 Hz) Rectified to DC	31400	26 VA	14 VA	F 155°C	IP 65 with connector	3 spades DIN 43650 DIN 4400 VDE 0110
=	12 - 24 (DC)		8 Watts				

#### CONSTRUCTION

Body: Brass  
 Tube and internal parts: Stainless steel  
 Seals and gaskets: NBR (Optional FKM)  
 Moulded coil: Resin

#### REPAIR KIT

Coil	31400 + voltage
Complete plunger + O' rings	KITVMR010-NBR

#### OVERALL DIMENSIONS

